



TUBO PRIMOFLEX® HOSE 5/8" – 25 M

Tubo PrimoFlex® (5/8") 25 m. Resistente alla pressione. Pressione di scoppio: 24 bar. Ampia sopportazione delle temperature: da -20 fino a 65° C.



Codice prodotto **2.645-140.0**

Dati tecnici

EAN Code		4039784447608
Diametro		5/8"
Lunghezza del tubo	m	25
Colore		Giallo
Peso	kg	3,7
Peso comprensivo di imballaggio	kg	3,8
Dimensioni (L × P × A)	mm	370 × 370 × 85

12 anni di garanzia

- Durevolezza garantita

3 strati

- Non si attorciglia

Resiste fino a 24 bar

- Resistente e durevole

MACCHINE COMPATIBILI

- G 7.180
- K 2
- K 2 Classic
- K 2 Horizontal
- K 2 Horizontal VPS
- K 2 Power Control
- K 2 Power Control Home
- K 2 Premium
- K 2 Premium FJ
- K 2 Premium Power Control
- K 2 Universal
- K 2 Universal Edition
- K 3
- K 3 FJ
- K 3 FJ Home
- K 3 Horizontal Plus
- K 3 Horizontal Plus Home
- K 3 Power Control
- K 3 Power Control Home
- K 3 Premium Power Control
- K 3 Premium Power Control Home
- K 4 Black
- K 4 Black Home
- K 4 Classic
- K 4 Classic Home
- K 4 FJ Home
- K 4 Power Control Flex
- K 4 Power Control Flex Home
- K 4 Power Control eco!Power
- K 4 Universal Edition FJ
- K 4 Universal Edition T5
- K 4 WCM
- K 5 Basic
- K 5 Black
- K 5 Black T5
- K 5 FJ
- K 5 Power Control
- K 5 Power Control Flex
- K 5 Power Control Flex Home
- K 5 Premium Smart Control Flex Home
- K 5 Universal Edition WB
- K 5 WCM
- K 6 Black
- K 6 Black T5
- K 6 Special
- K 7 Power Flex
- K 7 Power Flex Home
- K 7 Premium Power Flex Home
- K 7 Premium Smart Control Flex
- K 7 Premium Smart Control Flex Home
- K 7 Smart Control Flex
- K 7 Smart Control Flex Home
- K 7 WCM
- K 7 WCM Car&Home
- K 7 WCM FJ
- KHB 18-46 Battery Set
- QC 7-18 Handheld